



NOTE!
 TERMINAL BOX CAN BE SIDE MOUNTED
 (LEFT OR RIGHT) BY REFITTING FEET
 90° IN APPROPRIATE DIRECTION.
 CABLE ENTRY CAN BE SUPPLIED IN
 ANY ONE OF FOUR POSITIONS AT
 90° INTERVALS.

CUSTOMER		
ORDER No.		
SERIAL No.		
FRAME SIZE		
Kw	R.P.M.	
Hz	PHASE 3	
VOLTS	POLES	
BRGS.	D.E	N.D.E
MOTOR NETT. WT. Kg.		
INSULATION CLASS		
TEMPERATURE RISE °C		
DESIGN AMBIENT TEMPERATURE °C		
HEATER WATTS & VOLTS (IF FITTED)		
- WATTS, - VOLTS		

REMARKS

BROOK CROMPTON
 PRELIMINARY

Large Industrial Motors
 Guiseley, LEEDS LS20 9NZ

ALL DIMENSIONS IN MILLIMETRES

FIRST ANGLE PROJECTION

BROOK CROMPTON

Large Industrial Motors
 GUISELEY, LEEDS, LS20 9NZ.

NOTE!
 2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT MOUNTED METRIC A.C. MOTOR
 TOTALLY ENCLOSED FAN VENTILATED.
 FRAME SIZE:- W-DF355S 4-POLE UP.

SCALE	1:10	DATE	DRG. No.	M20803
DRAWN	DHM.	15/5/97		
CHECKED	DHM.	15/5/97		
APPROVED	I.J.W.	15/5/97	REVISION:	DATE