


NOTE:-
 TERMINAL BOX CAN BE MOUNTED (TOP OR LEFT) BY REFITTING FEET AND LIFTING LUGS 90° IN APPROPRIATE DIRECTIONS. CABLE ENTRY CAN BE SUPPLIED IN ANY ONE OF FOUR POSITIONS AT 90° INTERVALS



CUSTOMER	
ORDER No.	
SERIAL No.	
FRAME SIZE	
KW	R.P.M.
Hz	PHASE 3
VOLTS	POLES
BRGS.	D.E. N.D.E
MOTOR NETT. WT.	Kg.
INSULATION CLASS	
TEMPERATURE RISE °C	
DESIGN AMBIENT TEMPERATURE °C	
HEATER WATTS & VOLTS (IF FITTED)	
- WATTS, - VOLTS	

REMARKS

BROOK CROMPTON
 PRELIMINARY

Large Industrial Motors
 Guiseley, LEEDS LS20 9NZ

ALL DIMENSIONS IN MILLIMETRES

FIRST ANGLE PROJECTION

BROOK CROMPTON

Large Industrial Motors
 GUISELEY, LEEDS, LS20 9NZ.

NOTE:
 2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT MOUNTED METRIC A.C. MOTOR TOTALLY ENCLOSED FAN VENTILATED. TERMINAL BOX MOUNTED ON RIGHT HAND SIDE VIEWED ON DRIVE END. FRAME SIZE: W-DF200LX (ALL POLES).

SCALE	1:6	DATE
DRAWN	M.E	17.6.99
CHECKED	J.M.L	17.6.99
APPROVED	J.M.L	17.6.99

DRG. No.	M21603		
REVISION:	A. M.E	DATE	9.7.99