



4 HOLES FOR 1" BOLTS

NOTE:-  
 TERMINAL BOX CAN BE TOP OR RIGHT  
 HAND SIDE MOUNTED BY REFITTING FEET  
 90° IN APPROPRIATE DIRECTION.  
 CABLE ENTRY CAN BE SUPPLIED IN  
 ANY ONE OF FOUR POSITIONS AT  
 90° INTERVALS.

CUSTOMER	
ORDER No.	
SERIAL No.	
FRAME SIZE	
HP	R.P.M.
Hz	PHASE 3
VOLTS	POLES
BRGS. D.E	N.D.E
MOTOR NETT. WT.	Kg.
INSULATION CLASS	
TEMPERATURE RISE °C	
DESIGN AMBIENT TEMPERATURE °C	
HEATER WATTS & VOLTS (IF FITTED)	
WATTS,	VOLTS

REMARKS

**BROOK CROMPTON**  
 PRELIMINARY

Large Industrial Motors  
 GILSELEY, LEEDS LS20 9NZ

ALL DIMENSIONS IN INCHES

THIRD ANGLE PROJECTION

**BROOK CROMPTON**

Large Industrial Motors  
 GILSELEY, LEEDS, LS20 9NZ.

NOTE!  
 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR INTENTION TO USE RIGID COUPLINGS AND DRIVEN MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD/D FLANGE FOOT MOUNTED INCH A.C. MOTOR TO NEMA STD. MG1. TOTALLY ENCLOSED FAN COOLED.  
 FRAME SIZE:- W-DF587Z-D.

SCALE	1:12	DATE
DRAWN	B.J.T.	1.12.97
CHECKED	B.J.T.	1.12.97
APPROVED	I.J.W.	1.12.97

DRG. No.	M20855
REVISION:	DATE